



INVERSOR ELECTRÓNICOS ONDA SENOIDAL MODIFICADA

Linea IOE - IOE2000D - 2000W con Display Digital Inverter Expert



888




Características

- Equipado con Display Digital y Salida USB
- Carcasa de aluminio anodizado para mayor durabilidad y mejor disipación de calor
- Alarma por baja carga: alerta si la batería cae debajo de 11 Volts
- Protección por baja carga: apagado automático si la batería cae debajo de 10.5 Volts
- Protección por sobrevoltaje: apagado automático si el voltaje de salida supera los 15 Volts.
- Protección por sobrecarga: apagado automático por cortocircuito o si las cargas superan los límites de funcionamiento del inversor
- Proteccion por sobrecalentamiento: apagado automático si la temperatura supera los límites aceptables
- Onda senoidal modificada de alta calidad, adecuada para artefactos electrónicos

USB E RoHS CE-LVD/EMC 1.5 YEAR LIMITED WARRANTY

AC Output Receptacles(optional)



Especificaciones

Model			IOE-200-12D		IOE-200-24D		IOE-2000-48D
Output	AC Voltage		230V		230V		230V
	AC Voltage Range		220~240V AC		220~240V AC		220~240V AC
	AC Regulation	±10%					
	Rated Power	2000W					
	Peak Power	4000W(few seconds)					
	Waveform	Modified Sine Wave					
	Frequency	50/60Hz±3					
	No Load Current Draw	≤ 1.1A					
	Efficiency	≥90%					
	USB	5V 500mA or 2.1A(optional)					
	LED Indicator	Green for power on, Red for power failure status					
	Cooling fan	By 30% loads or temperature control					
Digital display	Input voltage/output power						
Input	DC Voltage	12V		24V		48V	
	Voltage Range	9.5~16V DC		19~32V DC		38~64V DC	
	DC Connector	Battery cable BVR10*4ea		Battery cable BVR10*2ea		Battery cable BVR6*2ea	
Protection	Low Voltage Alarm	11±0.5V DC		22±1V DC		44±2V DC	
	Low Voltage Shutdown	9.5±0.5V DC		19±1V DC		38±2V DC	
	Reset Voltage after L.V.S	11.5~12V DC		23~24V DC		46~48V DC	
	Overload	Shut off output, auto.reset					
	Over Voltage Shut down	15±0.5V DC		30±1V DC		60±2V DC	
	Over Temperature	Shut off output automatically, auto.reset					
	Output Short-circuit	Shut off, auto.reset					
	Reverse Polarity	Fuse burn out					
	Replaceable Fuse	30A*8		15A*8		7.5A*8	
	Soft Start	Yes, 3~5s					
	Earth Leakage	Yes					
	Accessory	Remote Control	Optional				
Environment	Working Temp.	0~30℃= @ 100% load; 40℃=@50% load					
	Working Humidity	20%~90% RH non-condensing					
	Storage Temp., Humidity	-30~+70℃/-22~+158°F, 10~95%RH					
	Temp. Coefficient	10%~90% RH					
Safety&EMC	Isolation Resistance	-20℃ ~ +50℃					
	EMI Conduction & Radiation	I/P-O/P:100M Ohms/500VDC/25/70%RH					
	EMS Immunity	Compliance to EN55022 chass B, 72/245/CEE, 95/64/CE					
	LVD	Compliance to EN61000-4-2,3					
	E-mark	Compliance to EN60950, EN61558-1-2					
Other	N.W.(g)	3960g					
	Dimension(cm)	33*23*10cm					
	Packing	Gift box, 2 units/10.6Kg/Ctn(40*31.5*38cm)					
	Output Socket	A, B, C, E, F, G,H,I,J,K,L,M,N(optional)					